

FUEL REFORMING TECHNOLOGIES (BRIEFING SLIDES)

Robert Diltz Air Force Research Laboratory

SEPTEMBER 2009

<u>DISTRIBUTION STATEMENT A</u>: Approved for public release; distribution unlimited.

AIRBASE TECHNOLOGIES DIVISION
MATERIALS AND MANUFACTURING DIRECTORATE
AIR FORCE RESEARCH LABORATORY
AIR FORCE MATERIEL COMMAND
139 BARNES DRIVE, SUITE 2
TYNDALL AIR FORCE BASE, FL 32403-5323

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

			THE ABOVE ADDRESS.	alid OMB control nur	nber.							
1. REPORT DA		<i>YY)</i> 2 . R E	PORT TYPE		3. DATES COVERED (From - To)							
2 2 2 2			Conference Pres	sentation		01-JAN-2007 31-AUG-2009						
4. TITLE AND					5a. CONTRACT NUMBER							
Fuel Reformin	ng Technologie	s (BRIEFIN	G SLIDES)		FA4819-07-D-0001							
					5b. GRANT NUMBER							
					5c. PROGRAM ELEMENT NUMBER							
					62012F							
6. AUTHOR(S) Diltz, Robert					5d. PROJECT NUMBER							
Dillz, Robert					4915							
			5e. TA	TASK NUMBER								
				C1								
			5f. WO	of. Work unit number								
				4915C19C								
7 DERECEMIN	C ORGANIZATI	ON NAME(S)	AND ADDRESS(ES)			8. PERFORMING ORGANIZATION						
	earch Laborato		REPORT NUMBER									
	ologies Divisi											
139 Barnes Dr												
	orce Base, FL											
9. SPONSORIN	IG/MONITORING	AGENCY NA	AME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)						
Air Force Res	earch Laborato	ory				AFRL/RXQD						
	Manufacturing					11. SPONSOR/MONITOR'S REPORT						
	nologies Divisio	on				NUMBER(S)						
139 Barnes Dr	rive, Suite 2 orce Base, FL 3	32403 5323				AFRL-RX-TY-TP-2009-4569						
	ION/AVAILABILI		NT			111111111111111111111111111111111111111						
		pproved for	public release; distribution	on unlimited.								
13. SUPPLEME		irs Case # 09	9-143 Document contain	ns color image	es Forr	presentation at congregation at German						
			eptember, Karlsruhe, Ger		26. T 01 F	resentation at congregation at Cerman						
14. ABSTRACT												
						and the integration of these technologies onto						
deployed base structures. This presentation is to describe those efforts along with the capabilities and competencies that have come as a result of this program.												
1 6												
15. SUBJECT T	ERMS											
JP-8, fuel reforming, solid oxide fuel cell, catalysis												
16. SECURITY CLASSIFICATION OF: 17. LIMITATION OF 18. NUMBER 19a. NAME OF RESPONSIBLE PERSON												
a. REPORT	b. ABSTRACT	c. THIS PAG		ert Diltz								
THI.				PAGES		LEPHONE NUMBER (Include area code)						
U	U U U 15											

Reset





Fuel Reforming Technologies

Deployed Energy & Utility Systems – Overview










Reduce Deployed Footprint While Enhancing Operational Efficiencies And Maintenance Requirements

- 50% Reduction In Power Deployment Airlift
- 82% Reduction In Fuel Consumption
- Reduce / Eliminate External Fuel Requirements, Saves Lives Of Soldiers, Marines, Sailors, and Airmen

Mission

Conduct Exploratory, Advanced, and Applied Research To Develop Next Generation Deployed Energy and Utility Systems To Meet New and Evolving Warfighter Needs




<u>The Objectives:</u> Develop The Underlying Concepts in Advanced Heat and Mass Transfer, Catalysis and Surface Chemistry, and Energy Conversion For an Efficient and Compact Energy System


The Technical Approach: Applying Transport Phenomena Theories, Formulation, and Modeling; Computational and Experimental Fluid Dynamics; Catalyst Kinetics Modeling, Catalyst Chemistry and Surface Analysis, Reactions Thermodynamics Modeling, Novel Catalyst Materials Formulation, and Catalyst Coating On Substrate; Catalytic Reactor system Testing and Analysis; Synthesis of Panchromatic Sensitizers; And Experimentation and Analysis

To Accomplish These Goals: In-House and Contracted Research to Universities and Industry, Leveraging and Collaborating with National Laboratories and DoD Services

Multi-fuel Reformer







Objective

Develop Reformer System Capable Of Converting Liquid Fuels Into Hydrogen For More Efficient Use In Fuel Cell Stacks

Technology Challenges

- Novel catalyst materials formulation
- Catalytic reactor system testing and analysis
- Catalyst Coating On Metal Substrate
- Reactions Thermodynamics Modeling
- Process water recovery

Benefits to the Warfighter

- To Reduce Deployed Energy Systems Footprint While Enhancing Operational Efficiencies And Maintenance Requirements
- To Achieve 60% Reduction In Power Deployment Airlift (from 4 Sorties down to less than 2 Sorties)
- To Save 3400 Gallons Of Fuel/Day/1100men Deployment
- To Reduce Noise/Thermal Signature And Environmental Emissions






Advanced Heat and Mass Transfer

Advanced Heat and Mass & Transfer Technologies





Objective

Identify And Develop New Technologies To Enhance Heat And Mass Transfer In Deployed Energy Systems

Technology & Core Competency

- Microchannel and Matrix Technologies
- Transport Phenomena Theory, Formulation, And Modeling
- Computational And Experimental Fluid Dynamics
- Mechanical Design And Instrumentation
- Laboratory Experimentation And Analysis
- Collaboration With Academia And Industry

Benefits to the War Fighter

- Reduce Deployed Footprint While Enhancing Operational Efficiencies And Maintenance Requirements
- 50% Reduction In Power Deployment Airlift (From 4 Sorties Down To Less Than 2 Sorties Of C-130 Per 1100 Men)
- Increase In MTBF From 500 Hrs To 2200 Hrs.
- Savings Of 1800 Gallons Of Fuel/Day/1100 Man






Catalysis Technologies

Catalysis Technologies





Catalyst

Objective

Develop New Catalysis Technologies For Process Intensification To Enhance Performance of Deployed Energy Systems

Technology & Core Competency

- Catalyst Kinetics Modeling and Testing
- Catalyst Chemistry and Screening
- Surface Analysis and Chemistry
- Reactions Thermodynamics Modeling
- Novel Catalyst Materials Formulation
- Catalyst Coating On Metal Substrate
- Catalytic Reactor system Testing and Analysis

Benefits to the War Fighter

- 50% Reduction in Power Deployment Airlift (from 4 Sorties down to less than 2 Sorties of C-131 per 1100 men)
- Increase in MTBF from 500 hrs to 2200 hrs.
- Savings of 1800 gallons of fuel/day/1100man deployment (5,280 Gal. vs. 3,480 Gal.)
- Reduced Noise Signature (70 db vs. 120 db)



Process Intensification Impact




Reduced Steam Reformer Size By 10 Folds



Preliminary Test Results Comparison





The preliminary test results confirmed the benefits of using FT-Petroleum 50/50 mix over Petroleum JP-8:

- Due to the reduction in aromatics and sulfur contents, the mix test runs were conducted without the use of fractionation. This has the potential to eliminate the fractionation component and reduce the size of the sulfur removal component by 50%--less maintenance.
- The mixed blend behaved similarly to Petroleum JP-8, however, it burned cleaner and processed fuel at much lower temperatures without producing non-condensable aerosol.
- Achieved complete conversion with less CO₂ and no higher hydrocarbons than methane was detected. Methane and CO along with H₂ are fuels for the Solid Oxide Fuel Cell (SOFC).

Preliminary Test Results Comparison



Test Runs	H_2	СО	CH ₄	CO ₂	C ₂ H ₄	C ₂ H ₆	C ₃ H ₆	Steam Reformer Exit Temp				
	[mol%]	[mol%]	[mol%]	[mol%]	[mol%]	[mol%]	[mol%]	[C]				
Petroleum JP-8												
1	75.2 %	12%	0%	12.8%	0%	0%	0%	800				
2	72.4 %	11.9%	3.8%	11.8%	0%	0%	0%	716				
50/50 Petroleum JP-8 and FT JP-8 Mix												
1	75.0 %	12.4%	6.3%	6.3%	0%	0%	0%	640				

Reported Data are the Average of Multiple Test Runs Each

The preliminary test results confirmed the benefits of using FT-Petroleum 50/50 mix over Petroleum JP-8:

- Due to the reduction in aromatics and sulfur contents, the mix test runs were conducted without the use of fractionation. This has the potential to eliminate the fractionation component and reduce the size of the sulfur removal component by 50%--less maintenance.
- The mixed blend behaved similarly to Petroleum JP-8, however, it burned cleaner and processed fuel at much lower temperatures without producing non-condensable aerosol.
- Achieved complete conversion with less CO₂ and no higher hydrocarbons than methane was detected. Methane and CO along with H₂ are fuels for the Solid Oxide Fuel Cell (SOFC).




10kWe Lab Demo Unit



JP-8

Fuel Processor for Fuel Cell



10kWe Steam Reformer Design

